

ABSTRACT

A takeout for an I.S. machine includes a cooling tube which is displaceable between up and down positions.

- 5 Displace is controlled to correspond to the desired heat removal along the path of displacement.

67		89
68		89
69		89
70		89
71		89
72		89
73		89
74		89
75		89
76		89
77		89
78		89
79		89
80		89
81		89
82		89
83		89
84		89
85		89
86		89
87		89
88		89
89		89
90		89
91		89
92		89
93		89
94		89
95		89
96		89
97		89
98		89
99		89
100		89
101		89
102		89
103		89
104		89
105		89
106		89
107		89
108		89
109		89
110		89
111		89
112		89
113		89
114		89
115		89
116		89
117		89
118		89
119		89
120		89
121		89
122		89
123		89
124		89
125		89
126		89
127		89
128		89
129		89
130		89
131		89
132		89
133		89
134		89
135		89
136		89
137		89
138		89
139		89
140		89
141		89
142		89
143		89
144		89
145		89
146		89
147		89
148		89
149		89
150		89
151		89
152		89
153		89
154		89
155		89
156		89
157		89
158		89
159		89
160		89
161		89
162		89
163		89
164		89
165		89
166		89
167		89
168		89
169		89
170		89
171		89
172		89
173		89
174		89
175		89
176		89
177		89
178		89
179		89
180		89
181		89
182		89
183		89
184		89
185		89
186		89
187		89
188		89
189		89
190		89
191		89
192		89
193		89
194		89
195		89
196		89
197		89
198		89
199		89
200		89